## List of Barrier-free Facilities in CAS Headquarters Building Address : 8 To Wah Road, Yau Ma Tei, Kowloon, HK

1	Accessible Entrance/ Exit		
	(a)	Dropped kerbs at ground floor near main entrance of building	
2	Accessible Lift		
	(a)	Tactile guide path near passenger lift zone;	
	(b)	Handrails at sides of lift car;	
	(c)	Braille and tactile markings on lift control buttons;	
	(d)	Indication of main entrance floor in star shape;	
	(e)	Emergency alarm button in bell shape and in contrasting colour;	
	(f)	Indication light adjacent to intercom speaker with notice in both English and Chinese;	
	(g)	Illuminated visual indicator and audible signals to indicate the arrival of the lift car	
		and its direction of travel in Cantonese, English and Putonghua;	
	(h)	Warning strip in contrasting colour at the edge of door sills	
3	Accessible Toilet		
	(a)	Four grab rails on walls;	
	(b)	Grab rails on both sides of door;	
	(c)	Emergency call bell (with notice "Emergency call" in both English, Chinese and	
		Braille);	
	(d)	Audible or visual alarm signal;	
	(e)	Lever flushing handle;	
	(f)	Tap with lever handle for wash-hand basin;	
	(g)	Door with push-type or level type handle;	
	(h)	Door fastening (openable from the outside in case of any emergency)	
4	Accessibility Sign		
	(a)	International symbol of accessibility with wheelchair figure in white on a blue	
		background for the following areas:	
		i) Passenger lifts;	
		ii) Accessible toilets	

## List of Barrier-free Facilities in CAS Headquarters Building Address : 8 To Wah Road, Yau Ma Tei, Kowloon, HK

BFA Common Area		
(a)	Tactile guide path to reception counter;	
(b)	Wide security gate;	
(c)	Space allowed for maneuvering wheelchair in corridor and lobby;	
(d)	Staircase provided with handrails (with Braille and tactile information on directional	
arrow) on both sides of staircase;		
(e)	Tactile warning strips provided at landings and at both the bottom and top ends of	
staircase;		
(f)	Treads and walls of staircase in contrasting colours	
Accessible Route		
(a)	Clear width of route not less than 1 050 mm;	
(b)	Clear width of door not less than 800 mm;	
(c)	Free from protrusion hazards, steps, kerbs other than dropped kerbs or steep ramps	
	(a) (b) (c) (d) arrov (e) stairo (f) Accessit (a) (b)	